

0 mm 10 mm 20 mm 30 mm 40 mm 50 mm 100 mm 150 mm 200 m

250 m

1. ALL HYDRANT KERB, PAVEMENT & BOX MARKINGS SHALL BE WHITE (TO AS2700 Y14 WHITE) WITH ONLY PAVEMENT AND KERB MARKING TO CONTAIN GLASS BEADS. PAVEMENT MARKING TO BE THERMOPLASTIC 2. MARKER POSTS SHALL ONLY BE USED IN STREETS AND ROADS WHERE THERE IS NO KERB & CHANNEL OR AS DIRECTED. 3. THE NOTICE PLATE SHALL BE REFLECTORIZED ALUMINIUM WITH BLACK LETTERING ON A WHITE BACKGROUND NOMINALLY 80mm x 80mm. MARKER POSTS SHALL BE POSITIONED AT THE FRONT OF THE PROPERTY BOUNDARY OPPOSITE THE FITTING. 5. DIMENSIONS ARE IN MILLIMETRES UNLESS SHOWN OTHERWISE. BLUE DELINEATOR MARKER TO COMPLY WITH AS1906.3 6. BLUE DELINEATOR MARKER TO BE INSTALLED ON ROAD CENTRELINE WHEN NO LINEMARKING OR RAISED PAVEMENT MARKERS EXIST. BLUE DELINEATOR MARKER TO BE INSTALLED IN ACCORDANCE WITH THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES WHEN LINE MARKING AND/OR RAISED PAVEMENT MARKERS EXIST 9. REFER TO T.S.C. S.D.313 'FIRE HYDRANT INSTALLATION DETAILS' 10. SIMILAR MARKINGS, POSTS, ETC. MAY BE USED FOR STOP VALVES (SV), SCOUR VALVES (SCV) & AIR VALVES (AV) EXCEPT THAT BLUE DELINEATOR MARKERS SHALL NOT BE USED ON ROAD OR POSTS. 11. THE DISTANCE TO THE HYDRANT IN METRES, TO AN ACCURACY OF 0.1m, SHALL BE PERMANENTLY MARKED ON THE PLATE WITH LEGIBLE NUMBERS A MINIMUMOF 80mm HIGH - REFER TO T.S.C. CONSTRUCTION S.D. 316

**JUNE 2015** 

ACAD FILE No: G:\\_AAA TSC STANDARD DRAWINGS\300 WATER SUPPLY\S.D.316 (June-15 Rev D).dwg